

AUFSITZEN UND LOS GEHT'S!
OPTIMA MINI-RIDER



Preis inkl. MwSt.

OPTIMA MINI-RIDER 76 RDE

	2.500 m² / 76 cm
	MTD, 1 Zylinder, 7,6 kW, 2.800 min ⁻¹ , 382 cm³, E-Starter
	Transmatic, 6 Gänge, 13" x 5", 16" x 6,5"
	150 l, Mulchkit (196-334-600) und Seitendeflektor als Zubehör erhältlich
	4,9 l
	38–95 mm, 5 Positionen
	1111-M6-0166
	L 192 / B 86 / H 112 cm
	144 kg
	A: 88 B: 98 C: 100 D: 5,0 E: 1,5 F: 1,0 G: 0,5
	 4 008423 873429 13A726SD600

	„SCHALTEN OHNE ZU HALTEN“ TRANSMATIC-ANTRIEB		NUR 46 CM WENDERADIUS FÜR HÖHERE FLEXIBILITÄT
	GROSSE UND KOMFORTABLE LUFTBEREIFTE RÄDER		SCHNELL UND EINFACH ZU BETANKEN
	SCHNITTHÖHEN- VERSTELLUNG & MÄHWERKS KUPPLUNG		DURCHSTEIGERAHMEN FÜR BEQUEMES AUF- UND ABSTIEGEN